

Cable Assemblies Made To Your Specifications



Pitch Connector Wire Assembly 3.96mm, 5.08mm pitch connector 3.96 mm and 5.08 mm

Key Specifications/Special Features:

- Woven Harnesses
- Operating Temperature -25 to +85 deg C
- Wide Range of Wire Harnesses Available



Connector Housings, Headers and Terminal Contacts

Key Specifications/Special Features:

- Wiring Accessories
- Wire to Board Dis-Connectable Connectors
- Wire to Board-In Connectors
- Wire to Wire Connectors
- Pin Headers, Terminals



2.54 mm Pitch Connector Wire Assembly

Key Specifications/Special Features:


- 2-20 Circuits
- Voltage Rating: 250V AC, DC
- Temperature Range -25 to +85 deg C
- Terminal Contact: Phosphor Bronze



2500 Series Pitch Dis-Connectable Connectors with 1500V AC/Minute Withstand Voltage at 2.5mm

Key Specifications/Special Features:

- 2-15 Poles
- Voltage Rating: 250V AC, DC
- Temperature Range -25 to +85 deg C
- Board Thickness 0.63" (1.6mm)



Full Range of Various Kinds of Connector Wire Harnesses

Key Specifications/Special Features:

- A Wide Range of Wire Harnesses Available
- Custom-Made According to Your Detailed Specifications
- Guaranteed High-Quality

Peter Parts Electronics, Inc has a wide range of custom cable assemblies available. For more detailed information, please contact us.

E-Mail: sales@peterparts.com • Phone: 585-265-2000 • Fax: 585-265-2542