


UC12G-107AP

Type	Unit	UC12G-107AP
Rated Voltage	V	1.5
Operating Voltage	V	1-3
*Rated Current(MAX)	mA	40
*Min Sound Output at 10 cm	dB	75
Coil Resistance	Ω	16 \pm 4
*Resonant Frequency	Hz	2048
Operating Temperature	$^{\circ}$ C	-20 - +70
Storage Temperature	$^{\circ}$ C	-30 - +80
Housing Material		NORYL
Weight	g	2


*Value Applying at Rated Voltage (resonant frequency, 1/2 duty, square wave)


FREQUENCY RESPONSE:



DIMENSIONS:

UNIT:mm
Tolerance: \pm 0.5mm






UC12G-107BP

Type	Unit	UC12G-107BP
Rated Voltage	V	1.5
Operating Voltage	V	1-3
*Rated Current(MAX)	mA	40
*Min Sound Output at 10 cm	dB	75
Coil Resistance	Ω	16 \pm 4
*Resonant Frequency	Hz	2400
Operating Temperature	$^{\circ}$ C	-20 - +70
Storage Temperature	$^{\circ}$ C	-30 - +80
Housing Material		NORYL
Weight	g	2.0

*Value Applying at Rated Voltage (resonant frequency, 1/2 duty, square wave)

FREQUENCY RESPONSE:



DIMENSIONS:

UNIT:mm
Tolerance:±0.5mm

